

VPL-PX15/PX11/PS10
LCD Data Projector

Get connected...
Get noticed.



this is not a rehearsal.

www.sonypresentation.com

SONY

Sony presents
three compact,
versatile ways
to enhance your presentation
effectiveness.



VPL-PX15 VPL-PX11 VPL-PS10



High Brightness and

- The VPL-PX15, VPL-PX11 and VPL-PS10 combine the latest LCD-panel technology with a 200 W UHP lamp to provide an outstanding combination of on-screen image quality and brightness. All three models feature three 0.9-inch LCD panels; the VPL-PX15 and VPL-PX11 providing a light output of 2000 ANSI lumens with true XGA (1024 x 768) resolution, while the VPL-PS10 provides 1500 ANSI lumens with true SVGA (800 x 600) resolution. High-quality images can be projected even in conditions of high ambient light.



Sophisticated Design

The sleek and elegant look of the VPL-PX15/PX11/PS10 adds style to any presentations, impressing the audience. During the presentation the built-in height adjuster ensures the optimum projection angle, and projector noise is not a distraction – the VPL-PX15/PX11/PS10 runs very quietly with the exhaust positioned on the front of the unit so that the discharged air is kept away from the audience.



Control Panel

Resolution




Flexible Use



VPLL-CW10*1

Short focal length
converter lens
Throwing distance*1: x 0.8



VPLL-CT10*2

Long focal length
converter lens
Throwing distance: x 1.2



Ceiling-mounted Projector

Installation Flexibility

The VPL-PX15/PX11/PS10 can also be floor mounted or ceiling mounted, in applications where a fixed installation is more appropriate. New optional converter lenses are available – easily attached to the standard lens, they enable the projector to be customised to virtually any application environment.

The VPL-PX11 also has two RGB inputs to allow multiple connection and an output to connect a local monitor. The integrated RS232C interface allows the easy connection to room control systems.

Portability


The VPL-PX15/PX11/PS10 is compact and is easy to carry with its retractable carrying handle. The projector can be carried around from room to room, bringing bright and clear images anywhere it is used.



Retractable Carry Handle

*1 Ratio of the lens' throwing distance to that of the standard lens.

*2 Standard lens should be set to its maximum zoom when using the VPLL-CT10.



VPL-PX15, VPL-PX11 and VPL-PS10 – A new line of portable projectors

The new VPL-P series from Sony provides excellent resolution and brightness as well as great flexibility. The VPL-PX15 and VPL-PX11 provide an outstanding brightness of 2000 ANSI lumens with true XGA resolution and handy features for installation use, while the VPL-PS10 provides 1500 ANSI lumens with SVGA resolution for excellent image reproduction. With the VPL-PX15, Sony brings networking capability to portable projectors – it is the first projector from Sony to provide wireless Peer to Peer (Ad-hoc) networking, offering a whole new style for smart, cable-less meetings in your company. Also incorporating a variety of useful functions, these stylishly designed, next-generation projectors will take your presentations to a higher level.

Innovative Presentations

with Network Projector VPL-PX15

Simulated picture



Wireless Peer to Peer (Ad-hoc) Presentations

The VPL-PX15 is the first of Sony projectors to include a wireless Peer to Peer (Ad-hoc) networking capability. Where a network environment is not provided, this technology enables a wireless Peer to Peer network to be set up using a wireless LAN PC Card*. This revolutionary application means that users can come to a meeting, set up a Peer to Peer network with their PCs and the projector, and run their presentations by communicating with and transferring data to the VPL-PX15. By doing away with the problem of cable connections between PC and projector, this development makes an important contribution to the smooth running of presentations and avoids the trouble of disconnecting and connecting PCs when several different presenters are involved.


* When using a wireless LAN PC Card, please confirm the safety regulations in each area.

LAN Connection


In offices with a network environment, the VPL-PX15 projector can connect to this LAN via a built-in 10Base-T/100Base-TX interface and then communicate with any PC on the LAN. The projector can also access the Internet directly using the pre-installed web-browser. A wireless infrastructure can also be provided with the use of a wireless LAN PC Card and an access point*. The LAN connection can also be used for controlling the projector via a Room Control System via TCP/IP.

* Recommended LAN PC Card, Wireless LAN PC Card, PC Memory Card and access point may vary by area. For details, please contact your nearest Sony office.


Wired



Wireless Infrastructure




Wireless Peer to Peer (Ad-hoc)





Application Software for Presentation Control

The VPL-PX15 is provided with Sony original Presentation Viewer, Image Viewer and File Manager application software. The Presentation Viewer enables users to prepare and run PowerPoint (PPT, PPS), Word documents (DOC) and Excel (XLS) presentation files, while the Image Viewer makes JPEG/GIF/BMP/PNG presentations possible. Presentation files in the projector memory can also be added or deleted using the File Manager.

Application select




File Manager



Presentation Viewer



Image Viewer



Setup

PC Presentations via Web Browser

Any PC within the same network can communicate with a VPL-PX15 via a web browser*. Via the NetMouse function you can control the mouse pointer of the projector to highlight points in your presentation.

E-Mail report function

Never run into a meeting and find out that the projector might be out of order. The VPL-PX15 is equipped with an E-Mail report function that will send out fault reports or status reports.

Remote Desktop compatibility

Display your Windows XP desktop directly on the projector via the network, and control any application remotely.**

* System requirements:

OS: Microsoft® Windows® 98, Windows 98 SE, Windows Me or Windows 2000

Web browser: Internet Explorer 4.0 or later or Netscape® Communicator 4.5x or 4.7x

** System requirements:

OS: Microsoft® Windows® XP, Windows XP Professional, for Remote Desktop only 256 colors are supported.

PC-less Presentations with Projector

Alternatively, it is not even necessary to use a PC to give presentations. When the projector is connected to the network, files shared in that network can be retrieved and opened for projection by using only the supplied remote control unit. Also with sufficient memory storage to save presentation files internally, presentation files can be saved in the projector prior to the meetings and then be projected off-line using the remote control unit. PC Card presentations are possible as well. Presentation files can be directly projected by inserting the PC Memory Card* into the PC Card slot.

* The PC Memory Card is not supplied with the VPL-PX15.





Other Features

Flexible Inputs

The VPL-PX15/PX11/PS10 accepts a wide variety of input signals, including composite video, S video and RGB, as well as computer signals up to SXGA. And with presets for 37 different signals, images can be reproduced in the most suitable signal mode in an instant.

USB Compatibility and Projector Station Software

The VPL-PX15/PX11/PS10 is USB-ready. With the USB connection, the projector can be controlled by a computer, using the Projector Station* USB application software. The software also helps with organization of presentation materials for quick access - registered files in the software can be opened with the Function keys on the remote control unit.



* PROJECTOR STATION version 3 software requirements: Microsoft Windows 98, Windows 98 SE, Windows Me or Windows 2000 operating system.

Useful Remote Control Unit

The VPL-PX15 is supplied with a laser pointer-equipped remote control unit, the RM-PJM15. The VPL-PS10 and VPL-PX11 are supplied with an RM-PJM12. Both these wireless control units include items such as Mouse function, Digital Zoom function and Freeze function. Presentations assigned in the Projector Station software can be opened with a push of the Function key. Also, when the VPL-PX15 is in NETWORK mode, the Function keys on the RM-PJM15 work as easy startup keys for the projector's network functions.



RM-PJM15

Freeze

The Freeze function displays a freeze-frame while preparing or switching to the next image. This can be controlled via the supplied remote control unit.

Stereo Speakers


The VPL-PX15/PX11/PS10 is equipped with two speakers, heightening the effectiveness of the presentations by adding stereo audio.



RM-PJM12

On-Screen Display

The OSD for projector control is available in nine languages: English, French, Spanish, German, Italian, Portuguese, Japanese, Chinese and Korean.



4-times Digital Zoom

Any part of the projected image can be zoomed in during a presentation, using the supplied remote control unit.



Digital Keystone Adjustment

Keystone distortion of up to ±15 degrees can be digitally corrected from the On-Screen Display or the supplied remote control unit. Images can be projected with the correct geometry even where installation space is limited.


APA (Auto Pixel Alignment)

With APA, single-button "press and play" operation correctly sizes and adjusts the display for optimum picture performance.

Input Signal Preset Data

No.	Resolution	fH (kHz)	fV (Hz)	H/V	
1	Video 60 Hz	15.734	59.940	N/N	
2	Video 50 Hz	15.625	50.000	N/N	
3	15 K RGB/Component 60 Hz	15.734	59.940	S on G	
4	15 K RGB/Component 50 Hz	15.625	50.000	S on G	
6	640x350	VGA-1	31.469	70.086	P/N
7		VGA VESA 85	37.861	85.080	P/N
8	640x400	NEC PC98	24.823	56.416	N/N
9		VGA-2/VESA 70	31.469	70.086	N/P
10		VGA VESA 85	37.861	85.080	N/P
11	640x480	VGA VESA 60	31.469	59.940	N/N
12		Mac 13	35.000	66.667	S on G
13		VGA VESA 72	37.861	72.809	N/N
14		VGA VESA 75	37.500	75.000	N/N
15		VGA VESA 85	43.269	85.008	N/N
16	800x600	SVGA VESA 56	35.156	56.250	P/P
17		SVGA VESA 60	37.879	60.317	P/P
18		SVGA VESA 72	48.077	72.188	P/P
19		SVGA VESA 75	46.875	75.000	P/P
20		SVGA VESA 85	53.674	85.061	P/P
21	832x624	Mac 16	49.724	74.550	N/N
22	1024x768	XGA VESA 43	35.524	43.479	P/P
23		XGA VESA 60	48.363	60.004	N/N
24		XGA VESA 70	56.476	69.955	N/N
25		XGA VESA 75	60.023	75.029	P/P
26		XGA VESA 85	68.677	84.997	P/P
27	1152x864	SXGA VESA 70	63.995	70.019	P/P
28		SXGA VESA 75	67.500	75.000	P/P
29		SXGA VESA 85	77.487	85.057	P/P
30	1152x900	SUN LO	61.795	65.960	N/N
31		SUN HI	71.713	76.047	C Neg
32	1280x960	SXGA VESA 60	60.000	60.000	P/P
33		SXGA VESA 75	75.000	75.000	P/P
34	1280x1024	SXGA VESA 43	46.433	43.436	P/P
35		SGI-5	53.316	50.062	S on G
36		SXGA VESA 60	63.974	60.013	P/P
37		SXGA VESA 75	79.976	75.025	P/P
38		SXGA VESA 85	91.146	85.024	P/P

Throwing Distance



VPL-PX15/PX11

Screen size*	40-inch	60-inch	80-inch	100-inch	120-inch	150-inch	200-inch	250-inch	300-inch
a	min.	mm 1458 2217 2977 3736 4495 5635 7533 9432 11330	inches 57 1/2 87 1/2 117 3/8 147 3/8 177 1/4 221 3/4 296 1/2 371 3/8 446 1/8						
	max.	mm 1764 2675 3586 4497 5408 6774 9052 11329 13607	inches 69 3/4 105 1/4 141 3/8 177 1/4 213 1/2 266 5/8 356 3/8 446 1/8 536						

VPL-PS10

Screen size	40-inch	60-inch	80-inch	100-inch	120-inch	150-inch	200-inch	250-inch	300-inch
a	min.	mm 1461 2221 2982 3742 4503 5644 7545 9446 11348	inches 57 1/2 87 1/2 117 3/8 147 3/8 177 1/4 222 1/8 297 3/8 372 1/8 447						
	max.	mm 1767 2680 3592 4505 5417 6786 9067 11348 13629	inches 69 3/4 105 5/8 141 3/8 177 1/4 213 1/2 267 3/8 357 1/4 447 5/8 536 3/4						

* Viewable area, measured diagonally.

Optional Accessories

Projector Lamp
LMP-P202
(for replacement)



Projection Lenses
VPLL-CW10
(Short focal length converter lens)

VPLL-CT10
(Long focal length converter lens)



PrimeSupport *

The VPL-PX15, VPL-PX11 and VPL-PS10 come with a 2 year PrimeSupport after sales programme that's unique to Sony. PrimeSupport ensures total peace of mind while using your Sony projector, bringing you these valuable benefits:

- Phone-based guidance to help get the best out of using your Sony projector
- Target 2 week repair time with a loan unit if it's going to take longer, keeping you up and running
- Original manufacturer repairs by Sony
- Planned cost of ownership

* PrimeSupport is included with all products shipped to EU, Norway and Switzerland. If you require additional services or support for longer periods, upgrades to the above services can be arranged through your local Sony Sales Representative.

Specifications

MODEL	VPL-PX15	VPL-PX11	VPL-PS10
OPTICAL	Projection system 3 LCD panels, 1 lens projection system		
	LCD panel 0.9-inch- p-Si TFT LCD panel with Micro Lens Array 2,359,296 pixels (786,432 pixels x 3)		0.9-inch- p-Si TFT LCD Panel 1,440,000 pixels (480,000 pixels x 3)
	Projection lens 1.3 times manual zoom lens, F 1.7 to 2.1, f33.6 to 42 mm		
	Lamp 200 W UHP Lamp (LMP-P202)		
	Screen coverage 1 m to 7.5 m (viewable area, measured diagonally)		
SIGNALS	Light output 2000 ANSI Lumen		1500 ANSI Lumen
	Colour system PAL, SECAM, NTSC, NTSC 4.43, PAL-M, PAL-N		
	Resolution Video: 750 TV lines RGB: 1024 x 768 pixels (native)		Video: 600 TV Lines RGB: 800 x 600 pixels
	Acceptable signals RGB (FH: 15 to 91 kHz, FV: 43 to 85 Hz), 15 kHz component 50/60 Hz system, composite video, Y/C video		
GENERAL	Cabinet colour Silky Silver/Twilight Blue		
	Speaker Max. 0.5 W x 2 (Stereo)		Max. 2 W x 2 (Stereo)
	Power requirements Max. 300 W, Standby 4.2 W, Standby in Network Mode : 9 W		Max. 290 W, Standby 4.7 W
	Operating temperature 0 to 35° C		
	Operating humidity 35 to 85 %		
	Dimensions 325 (W) x 110 (H) x 285 (D) mm		
	Mass Approx. 5.3 kg		Approx. 4.9 kg
	Heat dissipation 1023.9 BTU		989.6 BTU
INPUTS/OUTPUTS	VIDEO IN • COMPOSITE Y/C IN Y C • AUDIO IN Phono type, 1.0 V p-p +/- 2dB, sync negative, 75 Ω Mini DIN 4 pin 1.0 Vp-p, +/- 2dB, sync negative, 75 Ω Burst 0.3 Vp-p, +/- 2dB PAL, 75 Ω Stereo mini Jack, 500 mV rms, impedance more than 47 kΩ		
	INPUT A • RGB/COMPONENT R/R-Y G G with Sync/Y B/B-Y SYNC/HD Composite sync Horizontal sync VD Vertical sync 1.0 to 5.0 Vp-p, high impedance positive/negative 1.0 to 5.0 Vp-p, high impedance positive/negative 1.0 to 5.0 Vp-p, high impedance positive/negative Stereo mini jack, 500 mV rms, impedance more than 47 kΩ		
	MOUSE INPUT 6-pin (female)		No
	INPUT B 10BASE-T/100BASE-TX		Same as input A
	PC Card slot PC Card slot Type II		Not available
	USB/HUB UP (B type female) x 1, Down (A type female) x 1		UP (B type female) x 1 No HUB
	RS232C PORT No		Yes (9-pin)
	CONTROL S IN/ PLUG IN POWER Stereo mini jack 5.0 Vp-p, plug in power DC5V		No
	RGB-OUT No		Yes, HD D-sub 15 pin (female)
	SAFETY REGULATIONS UL, cUL, DHHS, DNHW, FCC class A, NEMKO, CE (LVD, EMC), C-Tick, CCIB, VCCI, JEITA		
SUPPLIED ACCESSORIES Remote Commander RM-PJM15** (VPL-PX15 only)/PJM12 (VPL-PS10 and VPL-PX11 only), Signal Cable SMF-410: HD D-sub 15-pin to D-sub 15-pin, PS/2 Mouse Cable, USB Cable: A type to B type, USB Application Software Projector Station, AA size Battery (2), Strap for Remote Commander (VPL-PX15 only), Air Filter (for replacement), AC Power Cord, Operation Manual, Operation Manual for Networking (VPL-PX15 only), Installation Manual for Dealers, Specified/recommended PC Card/Wireless LAN Access Point List (VPL-PX15 only), Quick Reference Sheet, Lens Cap			
DIMENSIONS unit: mm (inches)			
			
CONNECTOR PANELS			
			
VPL-PX15	VPL-PX11	VPL-PS10	

Distributed by

- *1 ANSI lumens is a measuring method of the American National Standards Institute IT7.228.
- *2 Excluding protruding parts.
- *3 Laser Type: Class II
Wavelength: 645 nm
Output: 1mW
- *4 9 W if Network Board is enabled



©2002 Sony Corporation. All rights reserved. Reproduction in whole or in part without permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measures are approximate. Sony is a registered trademark of Sony Corporation. Microsoft, Windows and PowerPoint are registered trademarks of Microsoft Corporation. Netscape is a registered trademark of Netscape Communications Corporation. Macintosh is a registered trademark of Apple Computer, Inc. All other trademarks are the property of their respective owners.

CA-VPL-PX15/PX11/PS10/GB-12/03/2002

SONY