

TECH. SPECIFICATIONS

Version 1.0 November 2001

ENGLISH

DDX3216

AUTOMATED DIGITAL MIXING CONSOLE



www.behringer.com

DDX3216

Fully automated 32-channel 16-bus 24-bit digital mixing console

- ▲ State-of-the-art 32-channel 24-bit digital mixing console
- ▲ 32 full-fledged channels, 12 ULN (Ultra Low-Noise) mic preamps with analog inserts and switchable phantom power
- ▲ 16 busses, 8 aux sends and internal input/output patchbay for comprehensive routing options
- ▲ Fully featured dynamic and snapshot automation
- ▲ 17 ultra-precise, low-noise 100-mm motorized ALPS® faders
- ▲ Compressor/limiter plus gate on all 32 channels
- ▲ 4-band fully parametric EQ, sweepable high-pass filter and phase reverse on all 32 channels
- ▲ Additional delay on channels 1-16
- ▲ Four simultaneously operable effects processors with dozens of first-class algorithms, accessible from all 32 channels
- ▲ Additional compressor/limiter (switchable pre/post) and EQ for stereo main mix
- ▲ Two option slots, three power-packed options for unlimited connectivity (16-channel ADAT®, 16-channel TDIF, 8-channel AES/EBU)
- ▲ Analog feel, intuitive user interface
- ▲ High-power floating point DSP technology (32-/40-bit) ensures virtually unlimited internal dynamic range
- ▲ Ultra high-resolution 24-bit AKM® A/D and CRYSTAL® D/A converters
- ▲ Freely configurable level meters on all channels
- ▲ Channel controllers with LED rings control any of nine parameters, selectable per channel
- ▲ Four freely assignable analog outputs on balanced 1/4" TRS connectors
- ▲ Six master controllers with comfortable push-and-turn functionality
- ▲ Large, easy-to-read LCD display with adjustable contrast
- ▲ Synchronization via SMPTE, MTC or internal clock
- ▲ Dither, word length and noise shaping adjustable for digital main outputs
- ▲ MIDI and RS232 connectors allow communication with a PC or other devices
- ▲ Extensive MIDI implementation (MMC, program changes, control changes, MIDI sysex)
- ▲ PCM/CIA card slot for saving/loading various libraries and other settings
- ▲ Free PC software for data transmission and management downloadable at www.ddx3216.com (serial cable included)
- ▲ 19" rack-mounting kit included
- ▲ Comprehensive Web support area with downloads, tips, application examples and more: www.ddx3216.com
- ▲ Manufactured under ISO9000 certified management system

SPECIFICATIONS

Mono inputs 1-12

Microphone input	
Type	electronically balanced, discrete input stage
Connector	XLR
Gain	+10 to +60 dB (PAD = -20 dB)
Input impedance	approx. 1.5k Ω @ 1 kHz
THD + Noise	0.05 %, 20 Hz to 20 kHz, +60 dB gain, -42 dBu at input
Max. input level	+1 dBu (minimum gain)
S/N ratio	95 dB, 20 Hz to 20 kHz, gain 1, 0 dBu at input
Equivalent noise	-90 dB, 20 Hz to 20 kHz, input termination: 150 Ω
Crosstalk	< -85 dB (channel 1 against channel 2), +60 dB gain, -42 dBu at input

Line input

Type	electronically balanced
Connector	1/4" TRS connector
Gain	-10 to +40 dB (PAD = -20 dB)
Input impedance	approx. 16k Ω @ 1 kHz
THD + Noise	0.02 %, 20 Hz to 20 kHz, +20 dB gain, -20 dBu at input
Max. input level	+24 dBu (minimum gain)
S/N ratio	92 dB, 20 Hz to 20 kHz, gain 1, 0 dBu at input
Equivalent noise	-88 dB, 20 Hz to 20 kHz, input termination: 150 Ω
Crosstalk	< -90 dB (channel 1 against channel 2), gain 1, 0 dBu at input

Stereo inputs 13-16

Type	electronically balanced
Connector	1/4" TRS connector
Gain	-20 to +20 dB
Input impedance	approx. 20k Ω @ 1 kHz
THD + Noise	0.015 %, gain 1, 0 dB at input, measured at main out
Max. input level	+22 dBu (minimum gain)
S/N ratio	86 dB, 20 Hz to 20 kHz, gain 1
(measured at main out)	
Equivalent noise	-85 dB, 20 Hz to 20 kHz, input termination: 150 Ω
(measured at main out)	
Crosstalk	< -85 dB (channel 13 against channel 14), gain 1, 0 dBu at input

Main outputs

Type	servo-balanced
Connector	XLR
Output impedance	approx. 160 Ω @ 1 kHz
Max. output level	+16 dBu

Multi outputs

Type	servo-balanced
Connector	1/4" TRS connector
Output impedance	approx. 160 Ω @ 1 kHz
Max. output level	+16 dBu

Control Room outputs

Type	servo-balanced
Connector	1/4" TRS connector
Output impedance	approx. 160 Ω @ 1 kHz
Max. output level	+16 dBu

S/PDIF digital input/output

Input	
Connector	RCA
Special feature	Sample rate converter (32 to 50 kHz)

Output

Connector	RCA
Dither	16, 20 and 24 bits
Special feature	Noise shaping

Wordclock input/output

Input	
Connector	BNC
Input impedance	20 k Ω
Output	
Connector	BNC
Output impedance	30 Ω
Signal type	TTL level square wave

SMPTE input

Connector	XLR
Input impedance	20k Ω

RS232 port

Connector	9-pin DIN jack
Transmission	115,200 bauds, 8 data bits, 1 stop bit, no parity

System specifications

Sampling rate	44.1 and 48 kHz (internal and external)
Signal delay	<1.6 ms at 48 kHz, channel input against main out
Frequency response	20 Hz to 20 kHz, +/- 0.1 dB

Faders

Type	100-mm ALPS® motorized faders
Resolution	+12 from 0 to - ∞ dB (256 increments)

Converters

A/D converters	
Resolution	24-bit delta-sigma AKM®
Oversampling	128 times
Dynamic range	116 dB typ.
D/A converters	
Resolution	24-bit delta-sigma CRYSTAL®
Oversampling	128 times
Dynamic range	106 dB typ.

MIDI interface

Type	5-pin DIN jacks
Connectors	MIDI IN, MIDI THRU and MIDI OUT

Level meters

Channel	16-digit LED display
Main	2 x 16-digit LED display
Special feature	Peak-hold function (off, 0-29 s, and ∞)

Mono inputs 1-12, microphone

Sig LED	(minimum gain)
Clip LED	-46 dBu at input

Mono inputs 1-12, line

Sig LED	(minimum gain)
Clip LED	-25 dBu at input

Stereo inputs 13-16

Sig LED	+23 dBu at input (gain at center position)
Clip LED	-36 dBu at input
	+10 dBu at input

Accessories

ADT1616	16 (2x8) inputs and 16 (2x8) output, ADAT® digital interface (optical)
TDIF1616	16 (2x8) inputs and 16 (2x8) outputs, TDIF digital interface (25-pin D-Sub)
AES808	8 inputs and 8 outputs, AES/EBU digital interface (25-pin D-Sub)
ACB808P	19" interface box for AES808, with 4 x XLR inputs and 4 x XLR outputs

Power supply

Power consumption	approx. 68 W
Fuse	100 to 240 V ~: T 4 A H
Mains connector	Standard IEC receptacle

Physical

Dimensions (H * W * D)	approx. 6 1/2" x 17 1/4" x 22 1/2" (163 mm x 438 mm x 572 mm)
Weight (net)	approx. 29 3/4" lbs (13.5 kg)

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER is a registered trademarks. ALL RIGHTS RESERVED.

AKM™, ALESIS™, ALPS™, ANALOG DEVICES™, CRYSTAL™, TASCAM™, WINDOWS™, ADAT™, DTRS™ and SHARC™ are all registered trademarks of their respective owners, which are in no way associated or affiliated with BEHRINGER.

© 2001 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany

Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30
